# RECEIVED TOWN OF ACTON HISTORIC DISTRICT COMMISSION

OCT 1 4 2014

472 Main Street, Acton, MA 01720

# TOWN CLERK

### **CERTIFICATE 1422**

ACTON
Pursuant to Chapter 40C of the General Laws of Massachusetts and the Historic Districts Bylaw of the Town of Acton, the Acton Historic District Commission hereby issues a

#### **CERTIFICATE OF APPROPRIATENESS**

For the work described in the Application of the same number.

Applicant (or owner) Edward Flannery

Telephone <u>978-263-7569</u>

Address 544 Mass Ave

Email Flannery7@verizon.net

Location of Work Flannery Way.

District: Center \_ West X South

**Description of Proposed work**: Construction of (2) new duplex residences on Flannery Way – an access road to property behind 544 Mass Ave which is within the Historic District.

### Findings, conditions, requirements, recommendations:

# Finding:

The Acton HDC found that the front elevation of each duplex was visible from the public way (Mass Ave ) and is therefore under the jurisdiction of the HDC.

# Requirements:

- Windows on front elevations to be wood units with integral (minimum) 5/4 x 4 wood casings and 2/1 simulated divided lites in 2 groups of 3 windows each per elevation. Wood window sills to be "historic" size and can be a composite material. Window sills on multiple units should be continuous.
- Water table detail to match submitted drawings.
- 1x10 Cornerboards approved, not smaller.
- Owner to install cedar clapboards, wood stair railing and wood balusters on front elevation.
- Owner may use composite material for the decking and stairs.
- New porch columns to have both base and cap detail.
- (4) garage brackets total 36 x 36 size W/ orch.
- Garage door to be model 921 plain with 6 lites.
- Front door to be Thermatru smooth star or equal with Simulated divided lights
- Exterior light fixtures to be plain square lanterns similar to attached.
- There will be no eave or rake returns.
- Architectural asphalt roof singles approved.

10f7

#### Recommendations:

It is recommended that the houses be painted shades of gray or white – as the monochromatic schemes of gray or white will minimize the impact of the garage doors.

When completed, the work outlined above must conform in all particulars to the Application approved on Sept 9, 2014, following a Public Hearing on the same date. The applicant may proceed with the proposed work provided all other approvals have been obtained, including a Building Permit or Sign License where required. This Certificate is valid for work commenced within one year of the date of issuance. An extension or renewal of the Certificate may be granted at the discretion of the commission. If a property changes ownership during the time the Certificate is in force, a new owner who wishes to continue the authorized work must apply to have a new Certificate issued in his or her own name.

Application received July 2, 2014 (and extended by owner)
Date of Public Hearing August 23 & continued Sept. 9, 2014

Certificate approved by [

Date Oct. 9, 2014

for Historic District Commission

Copies to: Applicant, Building Commissioner, Town Clerk, HDC File

Jof 7

- Bracket BKT 36x36x9 -I" X OCORNER BOA FOR BRACED WALL 8 -I" X 8" FRIEZE BOARI I" X 4" WINDOW TRIM ASPHALT SHINGLES 3' MIN. 8PACE REQ. .e" × 8" POST W/ ARCHITECTURAL JOHN J. FLANNERY INC. base icap - 14" Max from top of 8" BUILT OUT RAKE TYP. FRONT ELEVATIONS lot A-2 Mass Ave Acton, MA. September 9, 2014 cetificate # 1422 COPYRIGHT@2014 **BUILDING 1 & 2** DM-14-2-4 CONTINUOUS RIDGE VENT STEPS TO GRADE DRAWN BY: OWNER/ BUILDER SCALE: DATE SITE: INTEGRITY 498 GREAT ROAD ACTON, MA 01720 978.337.9378 DESIG "X O DIATOOR WITH WOOD OR C **WINDOWS TYPICA** ARDH FURK wood trim 生生のの子子の Coca CONTINUOUS RIDGE VENT MERICAN TRADITIONS SERIES BY HASS GARAGE DOORS MODEL 921 WITH GLASS TOP Cross bracing plann - no USE 921 | KID COLVERIES WITH IX CAP . 49 DEG I" X IO" WATER TABLE CONTINUOUS RIDGE VENT TEPS TO GRADE

Email








Save My Door

# Door Details



Get the look of fine painted wood and the strength of steel with a front door from the Smooth-Star<sup>®</sup> Entry Door Collection. It's an excellent value in a fiberglass entry door, made of rugged compression-molded fiberglass with deep detailed panels. This design creates beautiful shadows and contours on your door's surface.

This perfectly stylish yet rugged fiberglass front door resists the dents and dings from day-to-day traffic, and will never rust or corrode.

# **Divided Lite Options:**

-SDLGBG Simulated Divided Lites with Grilles

	Between Glass				
•	-SDL	Simulated Divided Lites			
	-GBGC	Grilles Between Glass with Contour Bars			
	-GBGF	Grilles Between Glass with Flat Bars			
	-RG	Removable Wood Grilles			

Themotru
Themotru
Smooth Star or
equal door w)
SDL grills.
NOT between Slaw,

More Divided Lite Details

**Fixed Grilles** 

-FXG

Fiberglass Entry Door Systems: Smooth-Star

#### About this entry door system

This entry door system is available with different features. The

417

# Brackets Coverarch

		Part Number	Projection (A)	Heigh (B)	Overnii Michi (C)	
Decor	7	BKT15X18X6	15"	18"	6"	
	17/	BKT19X24X4	18 5/8"	24"	4"	
		BKT19X36X4	19"	36"	4"	
	<b>I</b>	BKT20X24X5	20"	24"	5"	
	r	BKT25X25	25"	25"	4"	
	7	BKT28X30	28"	30"	3 1/2"	A B B B C C
**		BKT30X30	30"	30"	6"	
		BKT36X36	36 <sup>1</sup> /8"	36 <sup>1</sup> /8"	6ª	
	7	BKT31X30X5	31"	30"	5"	
	1	BKT19X31	19 ½"	31 1/2"	7 <sup>1</sup> /4"	A B C
	V	BKT24X36	24"	36"	3 ½"	
~	104		www.ty	PON.COM		59 T

RA 360 Series / 14/4" thick

Enjoy the handcrafted quality and rich traditional carriage house style without the maintenance of wood. The American Tradition Series™ doors contain CFC free polyurethane insulation with a calculated R value of 13.45. They are available in five base colors: white, almond, gray, sandstone and sahara tan. Overlay boards are glued and pinned to the door and painted white as standard. They are also available painted in the five base colors, with an option to mix and match. (example: almond boards on a sandstone door).

## Base Color Options

Polar White



The same of



Overlay Color Options

Polar White

Almond

4.00

775

Gray

Decorative Hardware

Handles (standard)




Hinges (optional)

# Top section design styles Frosted glass is available in all styles. 1/8' tempered is standard. 1/2' insulated tempered is optional.


Glazed Arch 3 page Glazed Arch 6 pane Solid Arch

Glazed 3 pane


Glazed 6 pane




Single doors




920 Plain (930 Arch)




922 Plain (932 Arch)



940 Plain (950 Arch)




941 Plain (951 Arch)




942 Plain (952 Arch)


#### Double doors




920 Plain (930 Arch)




940 Plain (950 Arch)




921 Plain (931 Arch)



941 Plain (951 Arch)



922 Plain (932 Arch)



942 Plain (952 Arch)

60f 7

